

The AV-12HB Teleprompter System



Applications/Key Benefits

- Extremely bright color display--can be read from up to 25'/8m away
- Excellent for outdoor use--very light-weight, mounts on jib
- Slide-adjusting, removable stacking 3lb/1.33kg weight included
- Quick-Release bracket allows the world's smallest break-down 12" Prompter
- Regulated 12V DC, 115V/60Hz or 230V/50Hz NTSC/PAL/SVGA flatscreen LCD monitor at 1,000 cd/m² and 500:1 contrast ratio
- Monitor designed and manufactured in USA at AVD's Melbourne FL facility
- NEW bottom-mount system for smaller cameras, requires no counterbalance weights

The AV12HB LCD Flatscreen Color CamMount Teleprompter features a 12"/30cm, 800x600 high-resolution color TFT LCD Active-Matrix flatscreen monitor with BNC Video In/Outputs and SVGA 15-pin computer input, aircraft-quality milled aluminum anodized hardware, and AVD's exclusive universal mounting system, which assures easy installation on any professional fluid head rated at 12lbs/5kg or more.

Lightweight soft-sided mirror hood is angle-adjustable and features a premium-quality glass 60/40 beamsplitter mirror. Image reversal for heads-up mirror display is done in the flatscreen monitor, and can be accessed from the included IR remote control. Brightness is 1000cd/m² Minimum weight is only 11lbs/5kg. Ships with a 3lb/1.33kg stacking counterbalance weight, all necessary mounting hardware and tools, and a 15'/8m high-quality connector cable.